

Edition 2.0



SQUIX
Made in Germany

Contents

Label printers SQUIX for industrial application	3
Type overview SQUIX 4	4
Technical details	5
Operation panel	6
Print heads	7
Print rollers	7
Interfaces	7
Technical data	8-9
Accessories	10-13
Applicator S1000	14-15
Applicator S3200	16
Dispensing module S5104	16
Mounting equipment SQUIX 4	17
Software	18
Stand-alone operation	18
Printer drivers	19
Programming / Integration / Administration	19
Maintenance / Service / Training	20
Product range	21-22
Product overview	23

All information on scopes of delivery, design and technical specifications correspond to the date of the printing. Subject to change.

*For current data see website
www.cab.de/en/squix*

Label printers SQUIX for industrial application



SQUIX are the further development of the successful A⁺ printers.

SQUIX represent

- innovative technology,
- easy operation,
- accuracy of impression,
- reliable and fast printing,
- compact, appealing design,
- highest quality standards.

The professional industrial label printers SQUIX can be used in a wide variety of applications. Their development is foremost focused on simple and convenient operation coupled with high reliability.

The print mechanics and housings are made of high-quality materials and perfectly match in terms of shape and function. A wide range of peripherals and software enable specific customized solutions.

Regardless of whether they are operated in stand-alone mode, in a PC application or in a network – the solid SQUIX printers are always up to the mark. A high-speed processor ensures fast printing processes and immediate label output.

Sample applications:

PCB labels

If there is only little space available
– smallest label size 4 x 4 mm



Type plates

Pin sharp 600 dpi fonts, graphics and barcodes



Cardboard box and pallet labels

Labels up to A6 format



Type overview

SQUIX 4

Material guide
left-aligned



1.1 Basic versions

For printing on labels and continuous materials, wound on rolls or fanfold. The material is torn off at the jagged tear-off edge. Optionally, it can be cut or externally rewound.



1.2 Dispensing versions P

In addition to the basic model the labels can be dispensed. The label is removed from the liner during the printing process. It can be removed manually or by applicator.

Delivery includes I/O interface

Material guide
centered



1.3 Basic versions M

For printing on all materials that are wound on rolls or reels resp. fanfold. Especially for very small labels and slim continuous materials such as pressed tubes. There is no need of adjusting the label width on the print head. For small materials adapted print rollers are offered.



1.4 Dispensing versions MP

In addition to the basic model the labels can be dispensed. The label is removed from the liner during the printing process. It can be removed manually or by applicator.

Delivery includes I/O interface



With RFID write/read device in preparation

1.5 HF according to ISO/IEC 15693 with 13.56 MHz

1.6 UHF according to ISO/IEC 18000-6C/EPC Class 1 Gen 2

When using Smart Labels, the integrated RFID chips are tested and qualified with data before printing. In case of an error the label is marked. To get good results in both writing and reading even when small labels are processed, the antenna position is centered just above the transponder.




1.7 Basic versions with separator MT

for continuous textile materials

Because of high heat energy while printing and the electrostatic charge of the materials the ribbon may stick with the textile tape. A separator guarantees reliable separation. It is recommended to select the print roller according to the maximum width of the textile tape resp. ribbon.

Technical details



*Label printer
SQUIX 4 MP*

1 Hinged cover

The two-part cover made of impact-proof plastics folds when opened. Only little footprint is needed. The large panoramic window allows to check the consumption of material and track the full printing process.

2 Solid metal chassis

Made of cast aluminum. All components are mounted on it.

3 Peel-off function

The label is removed from its liner via peel-off plate. High accuracy of printing and applying is achieved with the powered rewind assist and pinch rollers.

4 Peripheral connection

Add-on modules are easy to connect. All peripheral devices are plugged in the printer with two pins and fixed with a screw.

5 Ribbon holder

The three-part tightening axles enable a quick and easy exchange of ribbon.

6 Roll holder

The spring-mounted margin stop ensures constant tension during material feed, thus high accuracy of printing. For heavy rolls with core diameters of 76 or 100 mm an adapter is recommended.

7 Internal rewinder

With the rewinder labels or liners with or without a cardboard core can be rewound. The three-part tightening axle allows easy removal of the material.

8 Rocker

The resilient rocker with pulleys made of Teflon dampens the tension at print start, thus improving the accuracy of impression.

Operation panel

Intuitive and easy operation with self-explanatory symbols for configuration of the printer settings

Display

1 Power on

2 Headline

These functions are displayed:
receive print data, record data stream, ribbon warning,
USB memory stick, SD memory card, USB, LAN, WLAN,
Bluetooth, time

3 Status reports

Ready, pause, number of printed label per print job,
label in dispensing position, waiting for external start signal

Buttons

4 For options with the following functions

Cutter/perforation cutter: direct cutting
External rewinder: winding inside and outside
Tear-off or peel-off mode: printing of the next label
Applicator: application of the label

5 Operation

 Jump to menu

 Repetition of the last label

 Interruption and continuation of the print job

 Stop and deletion of all print jobs

 Label feed

USB plug-in / USB WLAN stick

6 For the service key or a memory stick, to load data into the IFFS storage


7 USB WLAN stick 802.11b/g/n 2.4 GHz included as an extra item in the scope of delivery



7

Example:

Print head settings



Printing parameters



Print speed with scroll function

Print position Y
slide control for fast adjustment
± keys for fine adjustment

Print heads



Print heads



All print heads are automatically detected and calibrated by the CPU. Major data like running performance, maximum operating temperature and heating energy are stored directly in the print head. The data can be read out at the plant.

Print heads type 4 - 300, 600 dpi

With a particularly sharp-edge print image;

They are suitable for type plates with small fonts and graphics.

They are, amongst others, required for resin ribbons with high energy needs.

Print heads type 4.3 - 200, 300 dpi

They are recommended especially for direct thermal printing and application in rough surroundings.

Print rollers

on the back of the device



Two types of material are provided for the different applications:

Print rollers DR4 – synthetic rubber coating;

They are suitable for high accuracy of impression and are provided as standard.

Print rollers DR4 M25/50/80 – synthetic rubber coating;

In the case of centered material guidance slim print rollers are needed for slim materials and ribbons. In this way, wear of print rollers, contamination of print heads and errors in material feed are avoided.

Print rollers DRS4 – silicone rubber coating;

They have an extra long service life with a higher tolerance of impression.

1 Plug-in for SD memory card

2 2 x USB host interfaces for keyboard, barcode scanner, USB memory stick, USB Bluetooth adapter

3 USB 2.0 Hi-speed device for PC connection

4 Ethernet 10/100 BASE-T

5 RS232C interface 1.200 to 230.400 baud/8 bit

6 3.1 I/O interface standard with dispensing device, accessory to basic device A PLC, a sensor or a hand switch start the labeling. At the same time, status and error messages are issued.

Compliant with IEC/EN 61131-2, type 1+3; all in- and outputs with galvanic isolation and reverse polarity protection, outputs in addition short circuit protected

Inputs PNP

Start printing and applying

Print first label

Reprint

Delete print job

Label dispensed

Interrupt labeling

Pause

Reset

Outputs PNP, NPN on request

Printer/applicator ready

Print job available

Applicator in basic position

Paper feed ON

Label in dispensing position

Applicator in applying position

Pre-warning end of ribbon

Common error

Technical data

		<input checked="" type="radio"/> Typical <input type="radio"/> Possible <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Option												
Device type	Material guide	Left-aligned				Centered								
Type of print head			4.3	4.3	4	4	4.3	4.3	4					
Printing method	Thermal transfer	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>					
Direct thermal		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input type="radio"/>					
Printable resolution	dpi	203		300	300	600	203	300	300					
Print speed	up to mm/s	250		250	300	150	250	250	300					
Print width	mm	104		108.4	105.7	105.7	104	108.4	105.7					
Printable area	Distance to locating edge	when left-aligned	mm	2.8	1.2	2.0	2.0	—	—					
		when centered	mm	—				Centered on material						
Material¹⁾														
On roll or fanfold:	paper, cardboard, ready-for-use tubes, plastics PET, PE, PP, PI, PVC, PU, acrylicate, Tyvec				<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>								
On roll, reel or fanfold:	pressed continuous tubes, textile, Smart Labels				—	<input checked="" type="checkbox"/>								
Labels	Width ¹⁾	mm	20 - 116				4 - 110							
	Height ¹⁾	mm	6 - 2,000				4 - 2,000							
	Thickness	mm	0.03 - 0.60				0.03 - 0.60							
Liner material	Width	mm	24 - 120				9 - 114							
	Thickness	mm	0.03 - 0.13				0.03 - 0.13							
Continuous material	Width	mm	24 - 120				4 - 114							
	Thickness	mm	0.05 - 0.50				0.05 - 0.50							
	Weight (cardboard)	up to g/m ²	300				300							
Pressed tube	Width ready-for-use	up to mm	120				114							
	Width continuous	mm	—				4 - 85							
	Thickness	up to mm	1.1				1.1							
Roll	Outer diameter	up to mm	205				205							
	Core diameter	mm	38.1 - 100				38.1 - 100							
Reel	Outer diameter	up to mm	—				205							
	Core diameter	mm	—				38.1 - 76							
	Outer width	mm	—				11 - 114							
Winding					Outside or inside		Outside or inside							
Ribbon²⁾														
Ink side					Outside or inside									
Roll diameter	up to mm		80											
Core diameter	mm		25.4											
Variable length	up to m		450											
Width ²⁾	up to mm		25 - 114											
Internal rewinder with dispensing device														
Outer diameter	up to mm		142											
Core diameter	mm		38.1 - 40											
Winding					Outside									
Printer sizes and weight														
Width x Height x Depth	mm		252 x 288 x 460											
Weight	kg		10											
Label sensor with position indication														
Gap sensor					For label front edge or punch marks and end of material									
Reflective sensor from below or top					For print mark front edge and end of material									
Distance sensor	to locating edge	Left-aligned	mm	5 - 60				—						
	from center to locating edge	Centered	mm	—				0 - 55						
Height of material passage	mm		2				2							
RFID														
Write/read device	HF ISO/IEC 15693, 13,56 MHz			—				<input type="checkbox"/>						
	UHF ISO/IEC 18000-6C/EPC Class 1 Gen 2			—				<input type="checkbox"/>						
Electronics														
Processor 32 bit clock rate	MHz		800											
Main storage (RAM)	MB		256											
Data storage (IFFS)	MB		50											
Plug-in for SD memory card (SDHC, SDXC)	up to GB		512											
Battery for time and date, real-time clock					<input checked="" type="checkbox"/>									
Data storage when power turned off (e. g. serial numbers)					<input checked="" type="checkbox"/>									
USB WLAN stick 802.11b/g/n 2.4 GHz					<input checked="" type="checkbox"/> (included as extra item in scope of delivery)									
Interfaces														
RS232C 1.200 to 230.400 baud/8 bit					<input checked="" type="checkbox"/>									
USB 2.0 Hi-speed Device for PC connection					<input checked="" type="checkbox"/>									
Ethernet 10/100 BASE-T					LPD, IPv4, IPv6, RawIP printing, DHCP, HTTP, FTP, SMTP, SNMP, TIME, NTP, Zeroconf, SOAP web service									
1 x USB host at the operation panel for					Service key or USB memory stick									
1 x USB host at the operation panel for					USB WLAN stick 802.11b/g/n 2.4 GHz									
2 x USB host on the back of the device for					Keyboard, barcode scanner, USB memory stick, USB Bluetooth adapter, USB WLAN stick 802.11b/g/n 2.4 GHz + a/n/ac 5 GHz with rod antenna									
WLAN 802.11b, g, n, access point or station mode	GHz		2,4 <input checked="" type="checkbox"/> / 5 <input type="checkbox"/>											
Peripheral connection USB host, 24 DC					<input checked="" type="checkbox"/>									
Digital I/O with 8 in- and outputs	Dispensing/basic device		<input checked="" type="checkbox"/> / <input type="checkbox"/>											

¹⁾ Limitations may apply to small labels, thin materials or strong adhesives. These applications need to be tested and approved.

²⁾ Ribbon at least according to width of label material in order to avoid folding.

Operating data		Graphics		
Power supply	100 - 240 VAC ~ 50/60 Hz, PFC	Graphic elements		
Power consumption	Standby <10 W / typical 150 W / maximum 300 W	Graphic formats		
Temperature / humidity	0 - 40°C / 10 - 85% not condensing	Barcodes		
Storage	0 - 60°C / 20 - 85% not condensing	Linear barcodes	Code 39, Code 93 Code 39 Full ASCII Code 128 A, B, C EAN 8, 13 EAN/UCC 128/GS1-128 EAN/UPC appendix 2 EAN/UPC appendix 5 FIM HIBC	Interleaved 2/5 Ident and lead code of Deutsche Post AG Codabar JAN 8, 13 MSI Plessey Postnet RSS 14 UPC A, E, E0
Transport	-25 - 60°C / 20 - 85% not condensing	2D and stacked codes	Aztec Codablock F DataMatrix PDF417 Micro PDF417 UPS MaxiCode QR code RSS 14 truncated, limited, stacked and stacked omnidirectional EAN/GS1 DataMatrix GS1 DataBar	All codes are flexible in height, modular width and ratio. Orientation 0°, 90°, 180°, 270° Options: check numbers, plain writing printout and start/stop code depending on type of code
Operation panel		Software		
Screen diagonal	Touchscreen LCD color display 4.3"	Programming	Direct programming with printer language JScript abc Basic Compiler Database Connector	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
Pixel W x H	272 x 480	Emulation	ZPL	<input type="checkbox"/>
Settings		Control	Printer control Administration Network Manager	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
	Region: languages country keyboard time zone Print Dispense Cut Apply	Ribbon direction of winding Ribbon pre-warning End of ribbon End of material Peripheral error	Label software	cablabel S3 Lite cablabel S3 Viewer cablabel S3 Pro cablabel S3 Print
On display		Ribbon remaining USB memory stick plugged in SD memory card plugged in	Also running with	CODESOFT NiceLabel EASYLABEL BarTender
	Digital clock Data reception WLAN field intensity Ethernet status Bluetooth status Data recording	Print head tension Print head temperature Print head open Pinch roller open (with dispensing version and separator)	WHQL certified Windows printer drivers for	Windows Vista Windows 7 Windows 8 Windows 8.1 Windows 10
			Windows	Server 2003 Server 2008 Server 2008 R2 Server 2012 Server 2012 R2
			Apple Mac drivers	OS X printer drivers valid from version 10.6
			Linux drivers	Valid from CUPS 1.2
			Stand-alone operation	
Testing				
System diagnosis	When device is switched on, including automatic print head detection			
Information display, status printout, analysis	List of fonts, list of devices, WLAN status, label profile, test grid, monitor mode, print data recorded on memory card			
Status reports	Printout of device settings, e. g. print length and runtime counter, machine status via software command, display of e. g. network errors - no link, barcode error, peripheral error etc.			
Fonts				
Font types	5 bitmap fonts including OCR-A, OCR-B and 3 vector fonts Swiss 721, Swiss 721 bold and monospace 821 internally provided, TrueType fonts loadable			
Character sets	Windows 1250 to 1257, DOS 437, 737, 775, 850, 852, 857, 862, 864, 866, 869, EBCDIC 500, ISO 8859-1 to -10 and -13 to -16, WinOEM 720, UTF-8, Macintosh Roman, DEC MCS, KOI8-R All Western and Eastern European characters, Latin, Cyrillic, Greek, Hebrew, Arabic, simplified Chinese and Thai characters are supported.			
Bitmap fonts	Size in width and height 1 - 3 mm Zoom factor 2 - 10 Orientation 0°, 90°, 180°, 270°			
Vector/TrueType fonts	Size in width and height 0,9 - 128 mm Zoom factor freely adjustable Orientation 360° in steps of 1°			
Font styles	Bold, italic, underlined, outline, inverse - depending on the font type			
Character pitch	Variable or monospace for steady character pitches			

Accessories

Overview

					● Typical ○ Possible □ Accessory	
Pos.	Printer add-ons	Basic device	Dispensing device	Left-aligned	Centered	
1.5	RFID HF 13,56 MHz	●	●	-	□	
1.6	RFID UHF 868/915 MHz	●	●	-	□	
1.7	Separator S400	●	-	-	□	
Extra equipment						
2.2	Print rollers DR4-M25, DR4-M50, DR4-M80	●	●	-	□	
2.3	Print roller DRS4	●	●	□	□	
2.6	Antistatic brush	●	●	□	□	
2.7	Adapter 100	●	●	□	□	
2.8	SD memory card 8 GB	●	●	□	□	
2.9	USB memory stick 8 GB	●	●	□	□	
2.10	USB WLAN stick 802.11b/g/n 2.4 GHz + a/n/ac 5 GHz	●	●	□	□	
2.11	USB Bluetooth adapter	●	●	□	□	
Dispensing labels						
2.12	Barcode tester for linear and 2D barcodes	-	●	□	-	
2.13	Present sensor PS800	-	●	□	□	
2.14	Present sensor PS900	-	●	-	□	
2.15	Present sensor PS1000	-	●	□	□	
2.16	Extended peel-off plate DP410	-	●	□	□	
Interfaces						
3.1	I/O interface	●	●	□	□	
3.2	I/O interface connector, SUB-D 25 pin	●	●	□	□	
3.3	Label selection - I/O box	●	●	□	□	
Connecting cable						
4.1	Connecting cable RS232 C, 9/9 pin, length 3 m	●	●	□	□	
Cutting, perforating, stacking						
5.1	Cutter CU400 with cutter tray	●	○	□	□	
5.2	Perforation cutter PCU400	●	○	□	□	
5.3	Stacker with cutter and base frame ST400	●	○	-	□	
Rewinding, unwinding labels						
6.1	Rewind guide plate RG400	-	●	□	□	
6.2	External rewinder ER4200	●	○	□	○	
6.3	External rewinder ER4300	●	○	□	○	
6.4	External rewinder EU4390	●	●	□	○	
Applicators and modules for dispensing						
7.1-7.5	Applicator S1000	-	●	□	□	
7.6	All-around labeler	-	●	□	□	
7.7-7.9	Applicator S3200	-	●	□	□	
7.10	Dispensing module S5104	-	●	□	-	
Mounting equipment						
8.1	Mounting plate	-	●	□	-	
8.2	Profile 40/80/120 mm	-	●	□	-	
8.3	Base plate 500 x 255 mm	-	●	□	-	
8.4	Floor stand 1600	-	●	□	-	
8.5	Printer holder	-	●	□	-	
Further A+ series accessories					Part no.	
	External rewinder ER1/210 ¹⁾	●	○	□	-	5948102.597
	External rewinder ER4/210	●	○	□	-	5948100
	External rewinder ER4/300	●	○	□	-	5946090
	External unwinder EU4/300	●	●	□	-	5946091
	Adapter kit for rewinders and unwinders ¹⁾	●	●	□	-	5978943
	Peel-off adapter PS5	-	●	□	-	5946120
	Present sensor PS6	-	●	□	-	5942353
	Pause adapter PS7	●	-	□	□	5946146
	Applicator A1000-220 ¹⁾	-	●	□	-	5949001.597
	Applicator A1000-300 ¹⁾	-	●	□	-	5949002.597
	Applicator A1000-400 ¹⁾	-	●	□	-	5949003.597
	Applicator A3200 ¹⁾	-	●	□	-	5976050.597
	Interface connector, SUB-D 15 pin	-	●	□	-	5917652
	Hand switch TR1 ²⁾	-	●	□	-	5942345
	Foot switch ²⁾	-	●	□	-	5535901
	Product sensor ²⁾	-	●	□	□	5941526
	Adapter screw M6/M4 ³⁾ SQUIX M6 to A4+/M4	●	●	□	□	5977586.001

¹⁾ Adjusted to SQUIX.
Adapter screw M6 on M4 to attach the external rewinder ER1/210, the applicators A1000 and A3200

²⁾ To be connected to PS5, PS6, PS7, A1000, A3200

Accessories

Extra equipment		Extra equipment	
2.2	 Print roller DR4-M25 Material width up to 25 mm; synthetic rubber coating for high accuracy of impression	2.6	 Adapter 100 For label rolls having a core diameter of 100 mm and an outer diameter larger 180 mm
		2.7	 SD memory card 8 GB
	Print roller DR4-M50 Material width up to 50 mm; synthetic rubber coating for high accuracy of impression	2.8	 USB memory stick 8 GB
	Print roller DR4-M80 Material width up to 80 mm; synthetic rubber coating for high accuracy of impression	2.9	 USB WLAN stick 802.11b/g/n 2.4 GHz + 802.11a/n/ac 5 GHz in station mode with rod antenna for extended reach
2.3	 Print roller DRS4 Material width up to 120 mm	2.10	 USB Bluetooth adapter
2.11	 Barcode tester for linear and 2D barcodes The accuracy of a horizontally and vertically printed barcode is tested by a camera directly after printing. In case of a faulty code the print job is stopped and the label can be removed. The barcode tester can be used in tear-off or dispensing mode or with an external rewinder. For further information see the operator's manual.		
Dispensing labels			
2.12	 Present sensor PS800 For dispensing devices with left-aligned material guide. The present sensor detects the label being in dispensing position. After the label has been removed the next label is automatically printed.		
2.13	 Present sensor PS900 For dispensing devices with left-aligned or centered material guide for example with circular labels whose trailing edges cannot be detected by the present sensors PS800 or PS1000 MP. After the label has been removed the next label is automatically printed.		
2.14	 Present sensor PS1000 For dispensing devices with centered material guide. The present sensor detects the label being in dispensing position. After the label has been removed the next label is automatically printed.		
2.15	 Extended peel-off plate DP410 For labels with a strong adhesive or very thick liner material that make its removal difficult. Only in connection with printing on demand button on the operation panel or control signal. A present sensor cannot be used.		
2.16	 Product sensor For automatic product detection on the conveyor belt; range 200 mm for the reflective sensor		
Interfaces			
3.2	 I/O interface connector, SUB-D 25 pin With screw clamps to connect all control signals to the I/O interface		
3.3	 Label selection - I/O box From a master controller like PLC up to 32 different labels can be selected from the memory card. The I/O box allows to realize simple PLC control processes with four in- and outputs via abc programming.		
Connecting cable			
4.1	 Connecting cable RS232 C, 9/9 pin, length 3 m		

Accessories

Cutting, perforating, stacking

5.1



Cutter CU400

To cut paper labels, self-adhesive labels, cardboard, textile or plastic materials as well as pressed tubes.

Cutter tray

Up to approximately 50 labels can be collected in the cutter tray.

Cutter	CU400
Material	Width up to mm
	120
	Weight cardboard gr/m ²
	60 - 300
	Thickness mm
	0.05 - 1.1
Cutting length	mm
	> 5
Gap height	up to mm
	2.5
Cuts	/min
	120
Stop print job if	
	Final cutter position not reached
Cutter tray	
Label height	up to mm
	100

5.2



Perforation cutter PCU400

Continuous materials like textile or pressed tubes are perforated in order to subsequently separate them manually.

In addition, the materials can also be cut.

Perforation cutter	PCU400
Material	Width up to mm
	85
	Weight cardboard gr/m ²
	60 - 300
	Thickness mm
	0.05 - 1.1
Cutting length	mm
	> 5
Gap height	up to mm
	2.5
Cuts	/min
	Cutting 120/perforating 150
Stop print job if	
	Final cutter position not reached
Perforating	Web width mm
	0.5
	Web distance mm
	2.5 or 10

5.3



Stacker with cutter ST400

Printed materials are cut and stacked. When the maximum stack height is reached, the print job is interrupted. With stiff or curved materials limitations may be possible. We recommend to have such applications tested at our plant. To place the devices on the table in any position.

Stacker with cutter	ST400
Material	Width mm
	20 - 100
	Weight cardboard gr/m ²
	60 - 300
	Thickness mm
	0.05 - 0.8
Cutting length	mm
	20 - 150
Gap height	up to mm
	1.2
Cuts	/min
	120
Stop print job if	
	Final cutter position not reached, paper jam, cover stacker open, stack height reached
Stack height	up to mm
	100



Storage table label W x H

Storage table and protective cover are adapted to the label size. They have to be ordered separately.

Accessories

6.1



Rewinding labels

with or without a cardboard core

Rewind guide plate RG400 for internal rewinder

Internal rewinding is for dispensing printers.

Thus, the peel-off plate is replaced by the rewind guide plate.

Rewind guide plate	RG400
Material width	up to mm 120
Roll diameter	up to mm 140
Tightening axle for core diameter	mm 38.1 - 40
Winding	Outside

6.2



External rewinder ER4200

The rewinder is screwed with the label printer. Labels are wound either inside or outside. The electronic swing arm control ensures consistent and tight winding.

External rewinder	ER4200
Material width	up to mm 120
Roll diameter	up to mm 205
Tightening axle for core diameter	mm 38.1 - 40
Winding	Outside or inside

6.3



External rewinder ER4300

The rewinder is screwed with the label printer. Labels are wound either inside or outside. The electronic swing arm control ensures consistent and tight winding.

External rewinder	ER4300
Material width	up to mm 120
Roll diameter	up to mm 300
Tightening axle for core diameter	mm 76
Winding	Outside or inside

6.4



Unwinding labels

External unwinder EU4390

Ensures consistent label feed with heavy rolls.

Both outside or inside wound rolls can be processed.

External unwinder	EU4390
Material width	up to mm 120
Roll diameter	up to mm 390
Core diameter	mm 38.1
with adapter	mm 76
Winding	Outside or inside

Applicator S1000

7.1



Real-time labeling

The applicator S1000 combined with a SQUIX is a cost-effective solution for all dispensing printers in semi-automatic operation or when vertically integrated in a production line. The label is placed on the product with a stroke cylinder.

1 Long service life

The ball-bearing guides are low-wearing.

2 Flexible product heights

With the stroke cylinder labeling is possible at different heights. Different stroke lengths are available.

3 Compressed air regulation unit

Micro filters prevent from contamination. The compressed air regulator ensures a permanent high quality of labeling.

4 High process reliability

Supporting air jet stream, induction air and stroke speed are adjustable. For sensitive products and packaging the pressing force can be reduced to less than 10N (1 kg). To avoid contamination, the vacuum holes are cleaned with air pressure after each labeling process.

5 Label sizes

Labels widths from 25 to 176 mm and heights from 25 to 200 mm can be processed.

6 Supporting air

Used for blowing the labels onto the pad

Pre-dispensing button

To test the labeling process. Pushing the button causes the label to be printed and held by the pad. Pushing the button again starts the labeling process.

Applicator	S1000-220	S1000-300	S1000-400
Cylinder stroke mm	220	300	400
Tamp stroke below device mm	64	144	244
Compressed air bar		4.5	

Accessories

7.2



Tamps

The labels are applied to the tamp and held there by vacuum. Tamp and label are then moved to the product by the applicator.

Universal tamp pads

The rasterized vacuum holes are covered by a foil and pierced according to the label size.

Tamp pad

Manufactured according to the label size

Type	Universal tamp pads		Tamp pad	
	A1021	A1021	A1021	M1021
Material guide	Left aligned Centered	Left aligned Centered	Left aligned	Centered
Tamp surface W x H mm	72 x 60	92 x 90	min. 72 x 60	
Label width mm	25 - 70	25 - 90	25 - 116	
Label height mm	25 - 60	25 - 90	25 - 200	
Product surface		Flat		
Product height		Variable		
Product during labeling		Not moving		

Accessories

Applicator S1000



Spring-mounted tamps

The spring deflection allows labeling even on inclined surfaces.

Universal tamp pads

The rasterized vacuum holes are covered by a foil and pierced according to the label size.

Tamp pad Manufactured according to the label size

Type	Universal tamp pads		Tamp pad			
	A1321	A1321	A1321	M1321		
Material guide	Left aligned Centered	Left aligned Centered	Left aligned	Centered		
Tamp surface W x H mm	116 x 102	116 x 152	min. 86 x 92			
Label width mm	25 - 116	25 - 116	25 - 116			
Label height mm	25 - 102	25 - 152	25 - 200			
Product surface	Flat					
Product height	Variable					
Product during labeling	Not moving					



Blow pad

In case of pressure-sensitive products the label can be blown on.

Thus, the blow pad moves to a fixed height. The product to be printed is positioned about 10 mm below.

Blow pad	A2021	M2021
Material guide	Left aligned	Centered
Tamp surface W x H mm	72 x 60	
Label width mm	25 - 116	
Label height mm	25 - 100	
Product surface	Flat	
Product height	Fixed	
Product during labeling	Not moving or in motion	



Roll-on pad

With the roll-on pad the label is moved right below the roll while printing. The pad moves to the product. The label is taken over by the product and rolled on during transport.

Roll-on pad	A1411
Material guide	Left aligned / Centered
Tamp surface W x H mm	120 x 80
Label width mm	25 - 116
Label height mm	80 - 200
Product surface	Flat
Product height	Variable
Product during labeling	In motion




All-around labeler

With the applicator labels can be applied to cylindric objects around the entire 360° circumference. The product is put on the rolls and labeling is started via hand or foot switch.

Tamp pad	A1021	M1021
Material guide	Left aligned	Centered
Tamp surface W x H mm	min. 72 x 60	
Label width mm	25 - 116	
Label height mm	25 - 140	
Product diameter mm	12 - 40	
Product surface	Cylindrical	
Product during labeling	In rotary motion	

Applicator S3200

7.7



Real-time labeling

The applicator S3200 combined with a SQUIX is a cost-effective solution for all dispensing printers in semi-automatic operation or when vertically integrated in a production line. With the S3200 printed labels are automatically applied on a product. By means of a rotary cylinder the label is positioned 45° to 95° to the horizontal and placed on the product with a short stroke cylinder.

Information on service life, pre-dispensing, compressed air regulation unit, process reliability and supporting air correspond with the applicator S1000 (see page 14).

Applicator	S3200
Rotary cylinder	45° - 95°
Stroke cylinder	up to mm 30
Compressed air	bar 4.5

Tamp pads or blow pads are manufactured according to the label size.

	Tamp pad		Blow pad	
	A3200-1100	M3200-1100	A3200-2100	M3200-2100
Material guide	Left aligned	Centered	Left aligned	Centered
Tamp surface W x H min. mm	72 x 60		72 x 60	
Label width mm	20 - 116		20 - 116	
Label height mm	5 - 80		10 - 80	
Product surface	Flat			
Product during labeling	Not moving		Not moving or in motion	

Dispensing module S5104

7.10



Dispensing module S5104

For labeling on packaging on a conveyor belt. The product sensor identifies the labeling position. Dispensing is started and at the same time the next label is printed. Conveyor belt speed and print speed have to be synchronized. A reflective sensor monitors the positioning.

Dispensing module	S5104
Material guide	Left aligned
Label width mm	25 - 116
Label height mm	25 - 200
Product surface	Flat
Product height	Fixed
Product during labeling	In motion, speed synchronized with the printer

Mounting equipment SQUIX 4



Mounting foot

To fasten the apply system and the product holder

1 Mounting plate

The apply system is fastened on the mounting plate.

2 Profile

Standard lengths 40, 80, 120 mm. The aluminum square profile can be manufactured in further lengths on request.

3 Base plate

To fasten the product holder
Standard size 500 x 255 mm

Floor stand

It enables the printer to be quickly and flexibly integrated in any production line. Height and width of the labeling position are easy to adjust in accordance with the product. Four guide rollers provide for mobility. The floor stand is adjusted with adjustable feet at the place of operation.

Floor stand	1600
Total height mm	1,600
Labeling height up to mm	1,400
Projection to center of label mm	230 - 500
Chassis W x D x H mm	600 x 860 x 140



8.5 Printer holder

The label printer is fixed on the mounting plate and quick-locked.

Software



Label software cablabel S3

It includes three functions:

- **design**
- **print**
- **monitoring**


As regards design, cablabel S3 opens up the full potential of the cab devices. The intuitive user interface provides an extensive instruction set, for example different date formats, mathematical or logic functions.

At this, cablabel S3 connects all cab marking systems. First of all you design your label. Only when it comes to printing you have to decide whether the label shall be dispensed on a label printer, a print and apply system or a marking laser system.

Do you want your marking system to print labels in stand-alone mode? cablabel S3 supports again. After the label has been designed the program supplies all necessary data to be stored within the printer for stand-alone mode.

cablabel S3 is of modular design and can be adapted to your requirements step by step. To support functions like, for example, native programming with JScript, elements like the JScript viewer are embedded as plug-in. The designer user interface and the JScript code are synchronized in real time. Special functions like the Database Connector or barcode testers can be comfortably integrated.

For further information see www.cab.de/en/cablabel



1 Toolbar

Here you can create different objects for your labels.

2 Tabs

For fast navigation between several opened label layouts.

3 Layers

Help to manage different label objects.

4 Designer

Streamlined design by WYSIWYG display of the label.

5 Printer spooler

Monitors all print jobs and shows status of printers.

6 Drivers

With integrated hardware drivers you can manage settings and communication with devices.



Stand-alone operation

This operating mode is the ability of the printer to select and print labels even when the device is not connected to a host system.

The label layout is designed with a label software like the cablabel S3 or via direct programming with a text editor on a PC. Label formats, fonts, texts and graphics as well as database contents are stored and read on a SD memory card, a USB memory stick or the internal data storage IFFS.

Only variable data are sent to the printer via a keyboard, barcode scanner, weighing systems or other host computers. These data are recalled from the host via Database Connector and printed.



Printer drivers

For printer control with a software other than cablabel S3 cab provides drivers in 32/64 bit for operating systems Windows Vista, Mac OS 10.6 (or newer) and Linux with CUPS 1.2.



WHQL certified Windows¹⁾ printer drivers

Our printer drivers are certified and signed by Microsoft. They ensure optimum stability on your Windows operating system.



Apple Mac OSX²⁾ driver

We provide a CUPS-based printer driver for programs using Mac OS X.



Linux drivers


Linux drivers are based on CUPS.

Printer drivers are available on the DVD delivered with your printer and for free download at www.cab.de/en/support



Database Connector

In stand-alone mode with network connection this program allows the printer to directly access data from a central ODBC- or OLEDB-ready database and have this data printed on the label. Simultaneously with the printing process, data can be rewritten to the database.



Programming



JS

To control your printer we have developed the embedded programming language JS. The programming manual for free download at www.cab.de/en



abc Basic Compiler

In addition to JS and as an integral firmware element the abc Basic Compiler allows advanced programming of the printer before the data are sent to editing for printout. In this way, for example external printer languages can be replaced without interfering in the current print job. Or you integrate data from other systems like a scale, a barcode scanner or PLC.

Integration



Printer Vendor Program

As a silver level partner in SAP's Printer Vendor Program cab has developed the replace method allowing easy control of cab printers with SAPScript from SAP R/3. At this, the host system only sends variable data to the printer. Graphics and fonts that priorly have been stored locally (IFFS, SD memory card, etc.) are merged.

Step 1

Creation of labels and replace file with the cablabel S3 software

Step 2

Implementation of replace file and replacement of variable data in SAPScript

Step 3

Printout from SAP

¹⁾ Windows is a registered trademark of Microsoft Corporation.

²⁾ MAC OS X is a registered trademark of Apple Computer, Inc.

³⁾ In preparation

Administration




Configuration in intranet and Internet

The HTTP and FTP server integrated in the printer via standard programs like web browser and FTP clients allows printer monitoring and configuration, firmware updates and memory card administration. The SNMP and SMTP client via email or SNMP datagram sends status, warning and error messages to administrators and users. Time and date are synchronized by a time server.



Network Manager³⁾

The Network Manager enables to manage several printers simultaneously within a network. It supports one-stop control, configuration, firmware update, memory card administration, data synchronization and PIN administration.



Maintenance



Label sensor

The label sensor is unlocked and pulled out with finger pressure for cleaning.



Print head

The print head can be exchanged in few steps. In general, adjustments and settings are not required.



Print roller

The print roller can be removed with a screw for cleaning or exchange.



Assembling tool

For replacing wear parts or peripheral mounting ONE tool is inserted at the printer ready to hand.

Service



Well-trained cab service engineers give worldwide support in maintenance and repair. Send your printer to a cab service center or a service partner selected by us. Your device will be checked and repaired within few workdays. If requested, a loan device is offered as a replacement during the time of repair.

You want maintenance and repair to be done in your company? Then make an appointment with our service department.

Contact: phone +49 721 6626 300, service.de@cab.de

Training



You enhance your knowledge of cab products for an effective use and gain valuable knowledge for the service and repair of the devices. At the Karlsruhe site, we offer training sessions on handling and operation, label design, software tools, printer drivers, programming, database connectivity, as well as for the integration in networks or a higher-level ERP systems. We will be happy to send you detailed information about the current training offering. Of course we also offer tailored trainings to your individual requirements - in Karlsruhe or at your site.

Product range

Label printers

Pos.		Part no.	Devices
1.1		5977014	Label printer SQUIX 4.3/200
		5977015	Label printer SQUIX 4.3/300
		5977001	Label printer SQUIX 4/300
		5977002	Label printer SQUIX 4/600
1.2		5977016	Label printer SQUIX 4.3/200P
		5977017	Label printer SQUIX 4.3/300P
		5977004	Label printer SQUIX 4/300P
		5977005	Label printer SQUIX 4/600P
1.3		5977018	Label printer SQUIX 4.3/200M
		5977019	Label printer SQUIX 4.3/300M
		5977010	Label printer SQUIX 4/300M
		5977011	Label printer SQUIX 4/600M
1.4		5977022	Label printer SQUIX 4.3/200MP
		5977023	Label printer SQUIX 4.3/300MP
		5977007	Label printer SQUIX 4/300MP
		5977008	Label printer SQUIX 4/600MP
		Part no.	Special devices
1.5		5977xxx.102	Printer with RFID HF, basic and dispensing version with centered material guide Label printer SQUIX x/xxxM-RFID/HF Label printer SQUIX x/xxxMP-RFID/HF "x" - choose device from Pos. 1.3/1.4
1.6		5977xxx.120	Printer with RFID UHF, basic and dispensing version with centered material guide Label printer SQUIX x/xxxM-RFID/UHF Label printer SQUIX x/xxxMP-RFID/UHF "x" - choose device from Pos. 1.3/1.4
1.7		5977xxx.355	Printer with separator, basic version with centered material guide Label printer SQUIX x/xxxMT "x" - choose device from Pos. 1.3
Scope of delivery: Label printer power cable type E+F, length 1.8 m connecting cable USB, length 1.8 m USB WLAN stick 802.11b/g/n 2.4 GHz operator's manual de/en			
DVD: Operator's manual in more than 20 languages configuration manual de/en/fr service manual de/en spare parts list de/en programming manual en WHQL certified Windows printer drivers for Windows Vista Server 2003 Windows 7 Server 2008 Windows 8 Server 2008 R2 Windows 8.1 Server 2012 Windows 10 Server 2012 R2 Apple Mac OS X drivers de/en/fr Linux drivers de/en/fr Label software cablabel S3 Lite cablabel S3 Viewer Database Connector			

Wear parts

Pos.		Part no.	Print heads
2.1		5977382.001	Print head 4.3/200
		5977383.001	Print head 4.3/300
		5977444.001	Print head 4/300
		5977380.001	Print head 4/600
		Part no.	Print and rewind assist rollers
2.2		5953700.001	Print roller DR4-M25
		5953701.001	Print roller DR4-M50
		5953702.001	Print roller DR4-M80
		5954180.001	Print roller DR4
		5954183.001	Rewind assist roller RR4
		5954985.001	Print roller DRS4

Accessories

Pos.		Part no.	Extra equipment
2.3		5977339.001	Antistatic brush
2.6		5959622.001	Adapter 100
2.7		5977370	SD memory card 8 GB
2.8		5977730	USB memory stick 8 GB
2.9		5977731	USB WLAN stick 802.11b/g/n 2.4 GHz + a/n/ac 5 GHz
2.10		5977732	USB Bluetooth adapter
2.11		5978911	Barcode tester for linear and 2D barcodes
		Part no.	Dispensing labels
2.12		5977585	Present sensor PS800
2.13		5977538	Present sensor PS900
2.14		5977735	Present sensor PS1000
2.15		5978908.001	Extended peel-off plate DP410
2.16		5978909	Product sensor

Accessories

Pos.		Part no.	Interfaces
3.1		5977369.001	I/O interface
3.2		5917651	I/O interface connector SUB-D 25 pin
3.3		5948205	Label selection - I/O box
		Part no.	Connecting cable
4.1		5550818	Connecting cable RS232 C 9/9 pin, length 3 m
		Part no.	Cutting, perforating, stacking
5.1		5978900	Cutter CU400 with cutter tray
5.2		5978901	Perforation cutter PCU400/2.5
		5978920	Perforation cutter PCU400/10
5.3		5978902	Stacker with cutter and base frame ST400
		5xxxxxx*	Storage table ST400, label W x H
		Part no.	Rewinding, unwinding labels
6.1		5978903.001	Rewind guide plate RG400
6.2		5978904	External rewinder ER4200
6.3		5978905	External rewinder ER4300
6.4		5978907	External unwinder EU4390
		Part no.	Applicators and dispensing modules
7.1		5976086	Applicator S1000-220
		5976087	Applicator S1000-300
		5976088	Applicator S1000-400
7.2		5949072	Universal tamp pad A1021 70 x 60
		5949075	Universal tamp pad A1021 90 x 90
		59xxxxx*	Tamp pad A1021 W x H
		5977xxx*	Tamp pad M1021 W x H
7.3		5949076	Universal tamp pad A1321 116 x 102
		5949077	Universal tamp pad A1321 116 x 152
		59xxxxx*	Tamp pad A1321 W x H
		5977xxx*	Tamp pad M1321 W x H

* User specific part no. following request

Pos.		Part no.	Applicators and dispensing modules
7.4		59xxxxx* 5977xxx*	Blow pad A2021 W x H Blow pad M2021 W x H
7.5		59xxxxx* 5977xxx*	Roll-on pad A1411 W x H Roll-on pad M1411 W x H
7.6		5976084	All-around labeler
7.7		5976085	Applicator S3200
7.8		59xxxxx* 5977xxx*	Tamp pad A3200-1100 W x H Tamp pad M3200-1100 W x H
7.9		59xxxxx* 5977xxx*	Blow pad A3200-2100 W x H Blow pad M3200-2100 W x H
7.10		5976083	Dispensing module S5104
		Part no.	Mounting equipment
8.1		5978910	Mounting plate
8.2		5958365 5965929 5971136	Profile 40 Profile 80 Profile 120
8.3		5961203	Base plate 500 x 255
8.4		5947400	Floor stand 1600
8.5		5978922	Printer holder
		Part no.	Label software
11.7		5588000 5588001 5588100 5588101 5588150 5588151 5588152 5588002 5588105 5588106 5588155 5588156 5588157 In preparation	cablabel S3 Lite cablabel S3 Pro 1 WS cablabel S3 Pro 5 WS cablabel S3 Pro 10 WS cablabel S3 Pro 1 additional licence cablabel S3 Pro 4 additional licences cablabel S3 Pro 9 additional licences cablabel S3 Print 1 WS cablabel S3 Print 5 WS cablabel S3 Print 10 WS cablabel S3 Print 1 additional licence cablabel S3 Print 4 additional licences cablabel S3 Print 9 additional licences cablabel S3 Print Server
1110		9009950	Programming manual en, printed copy

Product overview

Label printers MACH1/2
in the lower price segment



Label printers MACH4
where little space is available



Label printers EOS1
desktop device for label rolls
up to diameter 155 mm



Label printers EOS4
desktop device for label rolls
up to diameter 210 mm



Label printers A2+
industrial device
up to print width 57 mm



Label printers SQUIX
industrial device
up to print width 108 mm



Label printers A6+
industrial device
up to print width 168 mm



Label printers A8+
industrial device
up to print width 216 mm



Label printers XD4T
for double-sided printing



Label printers XC
for two-color printing



Print and apply systems Hermes+
for automation



Print and apply systems Hermes C
for two-color printing and applying



Print modules PX
to be integrated
in automatic labeling systems



Labels
of more than 400 materials



Ribbons
in wax, resin and resin/wax qualities



Label software cablabel S3
Design, print, monitoring



Label dispensers HS/VS
for horizontal or
vertical dispensing



Labeling heads IXOR
to be integrated
in labeling machines



Marking lasers FL+
with output powers 10 to 50 watt



Laser marking systems
for industrial solutions



① Headquarters and fabrication in Germany

② to ⑦ International subsidiaries

There are further 820 distribution partners in more than 80 countries.



Europe

Germany

cab Produkttechnik
GmbH & Co KG
Wilhelm-Schickard-Str. 14
76131 Karlsruhe
phone +49 721 6626 0
fax +49 721 6626 129
info@cab.de
www.cab.de

France

cab Technologies S.à.r.l.
2a Rue de la Moder
Z.A. Nord du Val de Moder
67350 Niedermosel
phone +33 388 722501
fax +33 388 722502
info.fr@cab.de
www.cab.de/fr

America

USA

cab Technology, Inc.
87 Progress Avenue Unit 1
Tyngsboro, MA 01879
phone +1 978 649 0293
fax +1 978 649 0294
info.us@cab.de
www.cab.de/us

Latin America

Alejandro Balmaceda
Hacienda Jurica Pte 1615
Colonial de Valle
32553 Juárez, Mexico
phone +52 656 682 4301
a.balmaceda@cab.de
www.cab.de/es

Asia

Taiwan

cab Technology Co., Ltd.
希愛比科技股份有限公司
16F-1, No. 700, Jhong Jheng Rd
Junghe, Taipei 23552
phone +886 (02) 8227 3966
fax +886 (02) 8227 3566
info.asia@cab.de
www.cab.de/tw

China

cab (Shanghai) Trading Co., Ltd.
铠博(上海)贸易有限公司
A507, No. 268, Tong Xie Rd
Shanghai 200335
phone +86 (021) 6236 3161
fax +86 (021) 6236 3162
info.cn@cab.de
www.cab.de/cn

Africa

South Africa

cab Technology (Pty) Ltd.
14 Republic Street
Bordeaux
2125 Randburg
phone +27 11 886 3580
fax +27 11 789 3913
info.za@cab.de
www.cab.de/za